

## ADHESIVE TAPICER

### PRODUCT

Adhesive TAPICER is produced from high quality materials. Basic ingredients used in the production process are SBS rubber, synthetic resins and modifying agents.

### APPLICATION

Adhesive TAPICER is intended for gluing polyurethane and polyester sponge, woven fabric, felt, jute, furniture rubber, carpets, etc. Its high durability has been confirmed by experiments in which the adhesive was used for concrete base, metal, raw and lacquered wood, asbestos-cement roofing material. All the materials mentioned above may be glued in different combination with one another.

### PROPERTIES

- ready for use
- creates flexible joint
- high efficiency
- unaffected by ageing

### TECHNICAL DATA

No.	Inspected property	Requirements
1.	Dry mass	42 % ± 3
2.	Viscosity (Ford's cube Ø6)	80 ÷ 120 s
3.	Specific gravity	approx. 0.8 g/cm <sup>3</sup>
4.	Colour	pink
5.	Open time	1 ÷ 20 minutes
6.	Tear off strength (PU foam – PU foam)	Degradation of at least 50% of the area glued

### INDICATIONS FOR APPLICATION

Mix thoroughly prior to use. The temperature of the materials glued and the adhesive shall be 18 – 25°C. Apply adhesive with a spray gun one-sided on flat surfaces and double-sided on high stress materials. Join the materials glued and press before the lapse of the open time.  
 Recommended jet diameter: 1.0 – 2.5 mm at spraying pressure 4 – 6 bars.  
 Adhesive efficiency 70 – 100 g/m<sup>2</sup>.

### STORAGE

Store in original packaging in dry, cool rooms (5-25 °C).  
 Protect against frost. Do not store in immediate vicinity of heat sources.

### PACKAGING

0.8l; 5l; 7kg; 15kg; 150kg.